

The Polypipe Sewerdrain Gravity Sewer System is a complete range in 200, 250 & 315mm solid wall PVCu Kitemarked to BS EN 1401-1.

Sewerdrain is suitable for all foul and surface water sewer applications and is fully compatible with 110 & 160mm BS EN 1401 drainage pipe & fittings.



Key Benefits

- Polypipe Sewerdrain is supplied complete with an integral seal for faster, problem free installation
- Lightweight and easy to handle for quicker installation
- Smooth external wall and bore pipe is available in both 3m and 6m lengths for reduced risk of blockage and improved flow
- Full range of fittings and adaptors to other sizes and materials
- Solid wall gives improved resistance to damage from cleaning and maintenance
- Fully adoptable under Sewers for Adoption and Sewers for Scotland.
- Carries the British Standard Kitemark to BS EN 1401-1

Methods of jointing

1. Where plain end pipe is being used, ensure that the pipe is cut square to the axis and that all burrs are removed.
2. Chamfer the end of the pipe to prevent the ring seal being damaged or displaced when the pipe is inserted into the socket. Fittings with spigot ends are moulded with a chamfer during manufacture.
3. Lubricate the spigot or ring seal with silicone grease or aerosol lubricant.
4. Insert the pipe or fitting into the socket and then withdraw it by approx. 10mm to allow for expansion of the pipework.