

Table 1) InfraWeb Panel Depth - Typical Recommended Application Traffic/ Load Classification

Pedestrians and Cycleways (non vehicular traffic)

Pedestrians, Cycleways and Small vehicles (≤ 1.5 Tonnes)

Cars, Vans etc (≤ 6 Tonnes)

Fire Engines, Removal and Refuse vehicles (\leq 20 Tonnes) Construction vehicles, Cranes etc.

NOTES

- 1. To be read in conjunction with project specification
- 2. Typical detail shown. A site specific assessment of the proposed pavement construction should be undertaken by suitabily qualified personel, considering expected vehicle trafficking and underlying ground conditions. Contact Polypipe Clvils' technical office for further information.
- 3. All dimensions in millimetres, unless otherwise stated.
- 4. All dimensions are nominal and may vary within manufacturing or construction tolerances
- 5. All site temporary and enabling works by others.
- 6. Polypipe products to be installed in accordance with Polypipe Civils recommendations, giving due consideration to the requirements of the approving organisation(s) and the ultimate owner of the installation.
- 7. This drawing is intended for guidance only. All proposed installations should be assessed in the context of the site and expected operational conditions, in addition to the overall site drainage scheme, prior to commencement of final design or construction activities.
- 8. All construction activities shall be executed by competent personnel, in accordance with all relevant legislation, regulations, standards or codes of practice.

REV AMENI	AMENDMENT			DATE		
RAWEB	FOR INFORMATION					
TECTION	SHEET SIZE A3		SHEET NO. 1 of 1		DRAWN BY SH	
CONCRETE BLOCK IB KERB EDGING	SCALE DATI		DATE 24	e 24/10/2018		
	IG-IW-SD-TRP-100-BP-K				REV.	