InfraWeb coarse aggregate i [Type 4/20 to BS EN 13242 BS EN 12620]				
NOTE Additional pinning of InfraWe proposed concrete infill perir required to prevent excessiv distention during infill operat	neter, may be e panel wall			
TYPICAL KERB R				
- Scale 1:20				
	Half Battered kerb, embeded into concrete bed Kerb haunch (Typically ST1 concrete to BS EN 206-1 and BS 8500-1) Kerb race (Typically ST1 concrete to BS EN 206-1 and BS 8500-1) Kerb race (concrete bed) formed in perimeter InfraWeb cells (webs cut to suit); See Detail 1 Soil graded to edging (if required)	 Min 50mm binder course (Typically AC14 open surf as max. 100/150 Pen to BS131 InfraWeb TRP 200 InfraWeb coarse aggregate in Infraweb panel (Type 4/20 to Polypipe ArborTex 300 Geot 	min 24mm depth) sphalt concrete; 08-1:2006) infill, surcharged above o BS EN 13242)	Treated timber edging (or similar acceptable edging), by others Edging supporting stake, by others
		- Scale 1:10		
All information in this document is of an illustrative nature and is s	upplied by Polypipe Civils without charge. Polypipe may modify and change the information, produ	cts and specifications from time to time for a variety of reasons.	Polypipe Civils	PROJECT POLYPIPE INFR TREE ROOT PROT DRAWING TITLE
without prior notice. Updates will not be issued automatically. This extent permitted by law), if you place any reliance on this documen products for a proposed application and expected site conditions;	information is not intended to have any legal effect, whether by way of advice, representation or w nt you must do so at your own risk. The information within this document should not be solely relier	varranty (express or implied). We accept no liability whatsoever (to the d upon to determine the suitability or installation requirements of our	North Road, Loughborough Leicestershire, LE11 1LE Tel: 01509 615100 Fax: 01509 615215 www.polypipe.com/civils	INFRAWEB TRP 200 C/W RES SURFACE AND HB KERB &

NOTES

- 1. To be read in conjunction with project specification
- Typical detail shown. A site specific assessment of the proposed pavement construction should be undertaken by suitabily qualified personel, considering expected vehicle trafficking and underlying ground conditions. Contact Polypipe Clvils' technical office for further information.
- 3. All dimensions in millimetres, unless otherwise stated.
- 4. All dimensions are nominal and may vary within manufacturing or construction tolerances.
- 5. All site temporary and enabling works by others.
- Polypipe products to be installed in accordance with Polypipe Civils recommendations, giving due consideration to the requirements of the approving organisation(s) and the ultimate owner of the installation.
- This drawing is intended for guidance only. All proposed installations should be assessed in the context of the site and expected operational conditions, in addition to the overall site drainage scheme, prior to commencement of final design or construction activities.
- 8. All construction activities shall be executed by competent personnel, in accordance with all relevant legislation, regulations, standards or codes of practice.

REV AMENDMENT					DATE		
RAWEB TECTION		FOR INFORMATION					
		SHEET SIZE A3	SHEET NO 1 O		DRAWN BY SH		
SIN BOUND GRAVE		SCALE DATI		DATE 12	E 12/09/2018		
	R EDGING	IG-IW-SD-TRP-200-RBA-K			REV.		